



Model	Hy-Ram 2000	Hy-Ram 2750	Hy-Ram 3000	Hy-Ram 4000	Hy-Ram 5000	Hy-Ram 7000	Hy-Ram 10000
<b>Piston weight</b>							
	kg 2.000	2.750	3.000	4.000	5.000	7.000	10.000
<b>Total weight with guiding</b>							
	kg 2.800	3.700	4.600	5.600	6.600	8.800	12.200
<b>Blows per min steplessly adjustable</b>							
	1/min 0-100	0-100	0-100	0-100	0-100	0-100	0-100
<b>Energy per blow, steplessly adjustable</b>							
	Nm 0-23.500	0-30.250	0-35.300	0-47.000	0-58.800	0-82.400	0-117.000
<b>Drop height, steplessly</b>							
	m 0-1,2	0-1,2	0-1,2	0-1,2	0-1,2	0-1,2	0-1,2
<b>Hydraulic-System</b>							
Working Pressure	bar 270	300	200	250	270	270	290
Flow rate	l/min 60-90	60-90	120-180	120-180	120-180	150-200	200-350
Required hydraulic power	kW 20-50	35-55	50-75	60-90	65-100	80-105	105-185
<b>Dimensions</b>							
Length A	mm 3.295	3.400	3.300	3.400	3.500	3.800	4.700
Length B	mm 4.495	4.600	4.500	4.600	4.700	5.000	5.900
Driving axis C	mm 435	450	500	500	500	600	650
Width D	mm 520	600	700	700	700	700	900
Pile weight (recomm.) soil-depende	ton up to 3,0	up to 3,5	up to 3,8	up to 4,4	up to 5,2	up to 5,8	up to 10,0
Electrical power	24 V DC / 8 A (for all types)						



**TESCAR SRL**  
 Via Flaminia II, 18 – 60027 Osimo (AN) ITALY  
 C.F. / P.IVA / Cod. Ident CEE / C.C.I.A.A. AN: IT 021 1666 042 0  
 Tel. 0039-(0)71-71.43.72 / 72.31.883 – Fax: 0039-071.71.44.16  
 e-mail: info@tescar.com – web-site: www.tescar.com