

	CF2B	CF4B	CF6B	CF8B
Tipologia di base richiesta <i>Required base type</i>	Terna <i>Backhoe loader</i>	Escavatore <i>Excavator</i>	Escavatore <i>Excavator</i>	Escavatore <i>Excavator</i>
Classe di peso richiesta <i>Required weight class</i>	8 ton <i>17637 lbs</i>	16 - 25 ton <i>35274 - 55115 lbs</i>	20 - 30 ton <i>44092 - 66138 lbs</i>	25 - 40 ton <i>55115 - 88184 lbs</i>
Coppia rotary <i>Rotary torque</i>	12 kNm <i>8830 ft lbs</i>	35/45 kNm <i>25800/33190 ft lbs</i>	65 kNm <i>47940 ft lbs</i>	85/100 kNm <i>62693/73756 ft lbs</i>
Velocità di rotazione <i>Drilling speed</i>	15 rpm	15 - 30 rpm	15 - 30 rpm	15 - 30 rpm
Velocità di scarico <i>Spin-off speed</i>	30 rpm	60 rpm	60 rpm	60 rpm
Corsa della rotary <i>Rotary stroke</i>	800mm <i>31,5 in</i>	1500mm <i>59 in</i>	2000mm <i>78,7 in</i>	2500mm <i>98,4 in</i>
Forza di tiro/spinta tramite martinetto <i>Push/Pull cylinder force</i>	35/60 kN <i>7868/13488 lbs</i>	80/130 kN <i>17984/29224 lbs</i>	150/200 kN <i>33721/44960 lbs</i>	150/230 kN <i>33721/51705 lbs</i>
Profondità massima <i>Max depth</i>	15m <i>49,2 ft</i>	25m <i>82 ft</i>	30m <i>98,4 ft</i>	35m <i>114,8 ft</i>
Diametro massimo - fronte mast <i>Max diameter - front mast</i>	600mm <i>23,62</i>	1000mm <i>39,37 in</i>	1200mm <i>47,24 in</i>	1300mm <i>51,18 in</i>
Diametro massimo suggerito - sotto mast <i>Max suggested diameter - under mast</i>	800mm <i>31,5 in</i>	1500mm <i>59 in</i>	2000mm <i>78,7 in</i>	2500mm <i>98,4 in</i>
Argano principale <i>Main winch</i>	1,5 ton <i>3372 lbs</i>	5 ton <i>11240 lbs</i>	7 ton <i>15736 lbs</i>	10 ton <i>22480 lbs</i>
Argano ausiliario <i>Auxiliary winch</i>	0,8 ton <i>1798 lbs</i>	1 ton <i>2248 lbs</i>	3,5 ton <i>7868 lbs</i>	5 ton <i>11240 lbs</i>
Peso (con kelly bar a bordo) <i>Weight (with kelly bar on board)</i>	2,5 ton <i>5511 lbs</i> 12m kelly bar	4,5 ton <i>9920 lbs</i> 15m kelly bar	6,5 ton <i>14330 lbs</i> 20m kelly bar	8 ton <i>17637 lbs</i> 25m kelly bar

Perché comprare un Kit TES CAR® B-SERIES?

- 1 — Può essere montato su qualunque escavatore (*) senza modificarne le funzioni originali.
- 2 — Permette un ampio sbraccio per perforare ad una notevole distanza dal centro ralla.
- 3 — Facile e rapido da montare e smontare per passare da trivella a escavatore, e viceversa.

Why buy a TES CAR® drilling kit B-SERIES?

- 1 — It can be mounted on any excavator (*) without modifying its original functions.
- 2 — It allows a wide reach to drill at a considerable distance from the center pillar.
- 3 — It's easy and quick to assemble and dismantle to switch from drill rig to excavator, and back.